

# **ARMATURE TEXTILE UTILISABLE POUR LA REALISATION DE COMPLEXES STRATIFIES ET COMPLEXES STRATIFIES EN FORME COMPORTANT UNE TELLE ARMATURE**

**Publication number:** FR2628448 (A1)

**Publication date:** 1989-09-15

**Inventor(s):** CHOMARAT GILBERT; LENGART JACQUES +

**Applicant(s):** CHOMARAT & CIE [FR] +

**Classification:**





**- international:** *B29C70/08; B29C70/46; B29C70/54; D04B1/00; D04H13/00; B29C70/04; B29C70/08; D04B1/00; D04H13/00; (IPC1-7): B29C51/12; B29D22/00; B32B27/04; D04H3/08*

**- European:** B29C70/08; B29C70/46C; B29C70/54C; D04B1/00; D04H13/00B3




**Application number:** FR19880003482 19880314

**Priority number(s):** FR19880003482 19880314

## **Also published as:**

 FR2628448 (B1)  
 EP0333602 (A1)  
 EP0333602 (B1)  
 CA1310178 (C)

## **Cited documents:**

 FR2048071 (A5)  
 US3044146 (A)  
 GB1370787 (A)

## **Abstract of FR 2628448 (A1)**

Armature textile pour la réalisation d'articles stratifiés du type constitué par au moins une nappe de fibres 1 disposées au hasard les unes par rapport aux autres, associée à une structure textile ordonnée 2, ces deux éléments 1, 2 étant liés entre eux par couture-tricotage caractérisée en ce que : - la nappe textile 2 à base de fils ordonnés est constituée par un tricot déformable; - le liage est réalisé de telle sorte que les jetées sur une aiguille 3 soient réalisées du côté du tricot 2 alors que les jetées sous plusieurs aiguilles 4 sont, quant à elles, réalisés côté nappe fibreuse 1.



Europäisches  
Patentamt  
European Patent  
Office  
Office européen  
des brevets

[Abstract of FR2628448](#)[Print](#)[Copy](#)[Contact Us](#)[Close](#)

## Result Page

Notice: This translation is produced by an automated process; It is intended only to make the technical content of the original document sufficiently clear in the target language. This service is not a replacement for professional translation services. The esp@cenet® Terms and Conditions of use are also applicable to the use of the translation tool and the results derived therefrom.

Textile reinforcement for the realization of laminated articles of the type consisted at least a fiber fleece 1 laid out randomly ones compared to other, associated a textile structure ordinate 2, these two elements 1, 2 linked between them by seam-knitting being characterized in that: - the textile web 2 containing ordered wire is consisted a deformable knitting - tying is carried out so that the piers on a needle 3 are produced side of knitting 2 whereas the piers under several needles 4 are, as for them, realized side fibrous web 1.

▲ top